

Pallet labelling system
PES



bornbinder® PES labelling system.
Labelling with normal A5 paper.
The labels are securely attached to
the cord. They are easy to remove
and can be re-used undamaged for
picking.



Pallets can
be tied
and labelled
in the same
operation.

Pallet labelling system PES

Pallets can now be clearly and conspicuously marked, without labels having to be glued or clipped to the pallet loads.

Service and maintenance

Our work does not finish upon delivery to the customer. Upon request, we make sure that the delivered systems are always kept at state-of-the-art level of technology. Or that immediate help is available in case of a malfunction. If you wish you can conclude a service agreement.

You also have the following services at your disposal:

- > Maintenance and modification (conversions/additions)
- > Repair or replacement of defective module

The most important advantages:

- > Pallet strapping and pallet labelling all in one pallet stop. Saves a lot of time.
- > Labelling on one to three sides possible.
- > Environmentally friendly, cost-effective consumable material: conventional twine and labels in A5 format made of normal paper.
- > Labels are directly fastened to the twine during strapping. No glued up boxes or labels sticking to the floor.
- > Paper labels can be removed from the twine without being damaged. Therefore use of the labels possible for picking.
- > Robust, simple and very low-wear design of the labelling machine for highest availability.
- > Large selection of label printers available.
- > Made-to-measure labelling software guarantees easy connection to different production planning and control systems (PPC).
- > Software and printer service by local company possible.
- > The elastic twine can be pulled off as an entire ring and used again for the return transport of the empties.
- > Low costs for consumable materials.
- > No waste of expensive PE foils.
- > Output: up to 140 pallets an hour.
- > Very easy machine operation. Does not require constant operating staff.
- > Infinitely variable height adjustment. Easy adaptation to any stack height.
- > Can be annexed to any conveyor belt.
- > Robust construction for continuous operation.
- > Extremely high degree of availability and low maintenance costs due to less wearing parts, combined with robust design.

bornbinder®

Born AG
Industriestrasse 19
CH-4800 Zofingen
Fon +41 62 746 99 55
Fax +41 62 746 99 44
E-Mail: info@bornbinder.com